

HYOSUNG HEAVY INDUSTRIES		INDUCTION MOTOR DATA SHEET		PROJECT No. 2492	
				MODEL No. 24EFFEB	
				L-SPEC No. D1ML8748	
SHEET 1 OF 1		CUSTOMER			
FOR INFORMATION		JOB NO.		ITEM No.	
SERVICE		SITE		QUANTITY	
GENERAL DATA			PERFORMANCE DATA		
FRAME No.		315S		OUTPUT 132 kW	
TYPE		EF		POLES 6 P	
ENCLOSURE		TE		ROTOR TYPE SQUIRREL CAGE	
COOLING METHOD		FC(IC411)		STARTING METHOD DIRECT ON LINE	
INSULATION CLASS		F CLASS		PHASE 3 PHASE	
TEMP. RISE AT FULL LOAD			FREQUENCY 60 Hz		
RES. METHOD		80 K (at S.F:1.0)		SPEED (AT FULL LOAD) 1195 r/min	
RATING		S1		PRIMARY	
LOCATION		INDOOR		VOLTAGE 380 V	
ALTITUDE		LESS THAN 1000 m		NO LOAD CURRENT 120.1 A	
HUMIDITY		LESS THAN 80 %		FULL LOAD CURRENT 260.1 A	
AMBIENT TEMP.		40 °C		LOCKED-ROTOR CURRENT 720 %	
EXPLOSION PROOF TYPE		Ex d IIB T4		EFFICIENCY	
MOUNTING		B3		AT 1/2 LOAD 92.8 %	
BEARING TYPE		ANTI-FRICTION		AT 3/4 LOAD 94.8 %	
NDE/DE BRG. No.		6316C3 / 6222C3		AT FULL LOAD 95.8 %	
BRG. LUBRICATION		MOBIL Polyrex EM		POWER FACTOR	
PROTECTION GRADE		IP55		AT 1/2 LOAD 65.5 %	
SERVICE FACTOR		1.0		AT 3/4 LOAD 75.5 %	
DRIVE		DIRECT COUPLED		AT FULL LOAD 80.5 %	
SHAFT			TORQUE		
EXTENSION		SINGLE		FULL LOAD 107.6 kg-m	
EXTERNAL THRUST		N/A		1055.6 N-m	
NOISE LEVEL(MEAN VALUE AT 1m FROM MOTOR)			LOCKED ROTOR 130 %		
NO-LOAD		N/A		BREAKDOWN 230 %	
VIBRATION		N/A		MOTOR GD² 18.688 kg-m²	
NUMBER OF CONSECUTIVE STARTS		N/A		MAX LOAD GD² AT MOTOR SHAFT 712 kg-m²	
ROTATION(VIEWED FROM DE)		C.C.W		MOTOR APPROX. WEIGHT 1330 kg	
ACCESSORIES (OPTIONAL)			PAINTING 0.5PB 3.2/4.4 (URETHANE)		
SUBMITTAL DRAWINGS					
TEMPERATURE DETECTOR			OUTLINE DIMENSION ES1AS30126		
WINDING			NO		
TYPE			-		
BEARING			NO		
TYPE			-		
SPACE HEATER			NO		
RATING			-		
APPLICATION STANDARDS			IEC60034-1, ISO 3746		
<NOTE> 1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARD. 2. EXCEPT FOR STATEMENTS SPECIFIED ON THIS SHEET, ANYTHING ELSE SHALL BE IN ACCORDANCE WITH MAKER STANDARD 3. THE TEMPERATURE MEASURED AT BEARING HOUSING DOES NOT EXCEED 105°C.			<REMARKS> 1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE. 2. PREMIUM EFFICIENCY TYPE MOTOR		
REV. NO		DATE		PREPARED	
1		2025-09-23		S.U.LEE	
CHECKED		APPROVED			
J.H.CHA		Y.J.PARK			

Data are subject to change without notice.(설계 개선 및 제작 환경에 따라 사전 공지 없이 특성 사양치 변경될 수 있음)

A4(210X297)