


1	
2	



M5*0.8
M6* 1
M8*1.25
M10*1.5
M12*1.75
M16* 2
M18*2.5
M20*2.5
M22*2.5
M24*3

HIGH RATIO NKF105C	CAPACITY (Kw)	0.4KW	WEIGHT (Kg)
	REDUCTION RATIO	1/150~1/1200	
	OUTPUT R.P.M	12~1.5	23

TOOTH CHAMFERING		MODULE						표기법 및 일반 공차	
		5	5-15	15					
HQ. T	C1	0.2	0.5	1.0				각도 : $\pm 0.2^\circ$	6 - 30 : ± 0.1
	C2	1.0	1.5	2.0				CHAMFER: C1,0	30 - 120 : ± 0.15
HC & HQ. I	C1	0.5	1.0	2.0				FILLET: R1,0	120 - 315 : ± 0.2
	C2	2.0	3.0	5.0				M=8(R0.1-1M)	M=8-15(R0.3M)
									1000 이상 : ± 0.5

	OUTLINE DWG						
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T	REMARK	
TITLE SPEC.	HIGH RATIO GEARED MOTOR 신크 NKFI05C-1/2HP 4P 신크 RATIO=1/150~1/1200	CUSTOMER NEW STANDARD TYPE					
DRAWN	KSS	SCALE	1 / 1	UNIT		mm	
DESIGN	YHH	DATE	2018.04.04	PROJECTION		☉ ☞	
CHECKED		REF. No.				REV. No.	△
APPROVED		DRAWING No.	KGM-NKF105C-HT-05-0D-000				
 (주) 케이지엠 KOREA GEARED MOTOR							